

Ironworkers | Cold Saws | Automatic Sawing Systems | Hydraulic Press | Pipe Notchers | Measuring Devices

# Upcut Miter sur Series

Large capacity precision mitering upcut saw for aluminum, non-ferrous metals, and plastic cutting. Available in 20" or 24" blade models.



#### **STANDARD FEATURES**

- Non-Ferrous saw
- Miter capabilities with fixed stops at 22.5°, 45°, 90°, 135°, and 157.5°
- Safety hood with safety interlock switch •
- Power hood (SUP-600 NF model)
- Blade door with safety interlock switch
- Dual palm buttons
- Adjustable feed rate on saw head
- Two horizontal pneumatic clamps
- Two vertical pneumatic clamps
- Capable of slotting



- Moveable back fence for larger capacity
- One gallon coolant
- Mist lubrication system
- One carbide tipped blade
- Air hose
- Chip collection drawer in base and 4-3/4" chip collection port
- Adjustable leveling pads
- Meets CE standards
- Three-year warranty on parts
- Made in Spain

CUTTING SPEEDS	
SUP-500 NF	3,000 rpm 5.5 hp (4.1 kW)
SUP-600 NF	3,000 rpm 5.5 hp (4.1 kW)


#### Optional Manual to Full Auto Feed Systems Available.

(See pages 43-46)

### SUP-500 NF

and the second


MAXIMUM CAPACITIES (With a 500 mm Dia Blade)		
	90 Degree	45 Degree
Round	7" (178 mm)	7" (178 mm)
Square	Square 6" (152 mm) 4-3/4" (121 mm)	
Rectangle	11-3/4" x 5" (298 x 127 mm)	5-3/4" x 4-3/4" (146 x 121 mm)



## SUP-600 NF

#### MAXIMUM CAPACITIES

(With a 600 mm Dia Blade)		
90 Degree 45 Degree		
Round	9" (229 mm)	9" (229 mm)
Square 8" (203 mm) 7" (178 mm)		
Rectangle	15" x 6" (381 x 152 mm)	10" x 4" (254 x 102 mm)




#### **SPECIFICATIONS**

	SUP-500	SUP-600
Motor Options (must specify)	230/460v, 3ph	
Air Pressure	90 psi	
Maximum Diameter Blade	500 mm	600 mm
Arbor Bore	50 mm	50 mm
Width	42" (107 cm)	49-1/4" (126 cm)
Depth	45-3/8" (115 cm)	54-1/2" (139 cm)
Height (top of the hood)	60-1/4" (153 cm)	64-3/8" (164 cm)
Height (floor to table)	38-5/8" (98 cm)	
Shipping Weight (may vary)	1,200 lbs. (545 kg)	1,465 lbs. (665 kg)

# **AngleMaster Upcut Miter**

## SUP-600 AngleMaster

MAXIMUM CAPACITIES		
(With a 600 mm Dia Blade)		
	90 Degree	45 Degree
Round	8" (203 mm)	7" (178 mm)
Square	Square 7" (178 mm) 6" (152 mm)	
Rectangle	9" x 5" (229 x 127 mm)	7" x 4-3/4" (178 x 121 mm)



SUP-600Motor Options (must specify)230/460v, 3phAir Pressure90 psiMaximum Diameter Blade600 mmArbor Bore50 mmWidth49-1/4" (126 cm)Depth54-1/2" (139 cm)	SPECIFICATIONS	
(must specify) 230/460v, sph   Air Pressure 90 psi   Maximum Diameter Blade 600 mm   Arbor Bore 50 mm   Width 49-1/4" (126 cm)		SUP-600
Maximum Diameter Blade 600 mm   Arbor Bore 50 mm   Width 49-1/4" (126 cm)		230/460v, 3ph
Arbor Bore     50 mm       Width     49-1/4" (126 cm)	Air Pressure	90 psi
Width     49-1/4* (126 cm)	Maximum Diameter Blade	600 mm
	Arbor Bore	50 mm
Depth 54-1/2" (139 cm)	Width	49-1/4" (126 cm)
	Depth	54-1/2" (139 cm)
Height (top of the hood) 64-3/8" (164 cm)	Height (top of the hood)	64-3/8" (164 cm)
Height (floor to table) 38-5/8" (98 cm)	Height (floor to table)	38-5/8" (98 cm)

CUTTING SPEEDS	
SUP-600 NF	3,000 rpm 5.5 hp (3.73 kW)

Large capacity upcut saw for aluminum, plastic, and non-ferrous metals. Combines an automatic mitering ability with a programmable feed.



This precision semi-automatic programmable sawing system automatically rotates to cut any angle, pushes material into the saw, then automatically rotates to the next desired angle.

#### **STANDARD FEATURES**

- Non-ferrous saw
- Semi automatic operation
- Mitering degree range 22° to 159°
- Feed length available 10' to 30'
- Right-to-Left feed only
- Touch screen controls
- Windows<sup>®</sup> based software (incudes profile screen)
- Unlimited job storage
- Powered safety hood with safety interlock switch
- Dual palm buttons
- Adjustable feed rate on saw head

- Two horizontal pneumatic clamps
- Two vertical pneumatic clamps
- Capable of slotting
- One gallon coolant •
- Mist coolant lubrication system •
- One carbide tipped blade
- Air hose
- Chip collection drawer in base and 4-3/4" chip collection port
- Adjustable leveling pads
- Meets CE standards •
- Blade door with safety interlock switch Two-year warranty on parts (saw)
  - One-year warranty on parts (feed system)
  - Saw Made in Spain
  - Feed system Made in USA

Straight Cuts – Miter Cuts – and Everything In-Between

#### **OPTIONAL FEATURE**

Auto 90° program allows machine to run in full auto mode when cutting at 90°.

# MACHINES THAT WORK AS HARD



Sales partner in México:



ACAT Mexicana Ave. Regio Parque #200 Regio Parque Industrial Apodaca , Nuevo León, México CP. 66633

acat@acatmexicana.com

nexicana.com 🕠 TEL. 8183548910 www.acatmexicana.com

Scalidhman