

Upcut Miter sup Series

Large capacity precision mitering upcut saw for aluminum, non-ferrous metals, and plastic cutting. Available in 20" or 24" blade models.



STANDARD FEATURES

- · Non-Ferrous saw
- Miter capabilities with fixed stops at 22.5°, 45°, 90°, 135°, and 157.5°
- Safety hood with safety interlock switch •
- Power hood (SUP-600 NF model)
- Blade door with safety interlock switch
- Dual palm buttons
- Adjustable feed rate on saw head
- Two horizontal pneumatic clamps
- Two vertical pneumatic clamps
- · Capable of slotting

- Moveable back fence for larger capacity
- One gallon coolant
- Mist lubrication system
- One carbide tipped blade
- Air hose
- Chip collection drawer in base and 4-3/4" chip collection port
- Adjustable leveling pads
- Meets CE standards
- Three-year warranty on parts
- · Made in Spain

SVR-WARRANTY

CUTTING SPEEDS


| SUP-500 NF | 3,000 rpm 5.5 hp (4.1 kW) |
|------------|------------------------------|
| SUP-600 NF | 3,000 rpm 5.5 hp (4.1 kW) |

Optional Manual to Full Auto Feed Systems Available.


(See pages 43-46)

SUP-500 NF

MAXIMUM CAPACITIES (With a 500 mm Dia Blade) 90 Degree 45 Degree Round 7" (178 mm) 7" (178 mm) Square 6" (152 mm) 4-3/4" (121 mm) Rectangle 11-3/4" x 5" 5-3/4" x 4-3/4"



SUP-600 NF




| SPECIFICATIONS | | | | |
|---------------------------------|---------------------|---------------------|--|--|
| | SUP-500 | SUP-600 | | |
| Motor Options (must specify) | 230/460v, 3ph | | | |
| Air Pressure | 90 psi | | | |
| Maximum Diameter Blade | 500 mm | 600 mm | | |
| Arbor Bore | 50 mm | 50 mm | | |
| Width | 42" (107 cm) | 49-1/4" (126 cm) | | |
| Depth | 45-3/8" (115 cm) | 54-1/2" (139 cm) | | |
| Height (top of the hood) | 60-1/4" (153 cm) | 64-3/8" (164 cm) | | |
| Height (floor to table) | 38-5/8" (98 cm) | | | |
| Shipping Weight (may vary) | 1,200 lbs. (545 kg) | 1,465 lbs. (665 kg) | | |

AngleMaster Upcut Miter

SUP-600 AngleMaster

| MAXIMUM CAPACITIES | | | |
|---------------------------|--------------------------------------|-------------------------------|--|
| (With a 600 mm Dia Blade) | | | |
| | 90 Degree | 45 Degree | |
| Round | 8" (203 mm) | 7" (178 mm) | |
| Square | Juare 7" (178 mm) 6" (152 mm) | | |
| Rectangle | 9" x 5" (229 x 127 mm) | 7" x 4-3/4" (178 x 121 mm) | |



Large capacity upcut saw for aluminum, plastic, and non-ferrous metals. Combines an automatic mitering ability with a programmable feed.



| SPECIFICATIONS | | |
|---------------------------------|------------------|--|
| | SUP-600 | |
| Motor Options (must specify) | 230/460v, 3ph | |
| Air Pressure | 90 psi | |
| Maximum Diameter Blade | 600 mm | |
| Arbor Bore | 50 mm | |
| Width | 49-1/4" (126 cm) | |
| Depth | 54-1/2" (139 cm) | |
| Height (top of the hood) | 64-3/8" (164 cm) | |
| Height (floor to table) | 38-5/8" (98 cm) | |

CUTTING SPEEDS

| SUP-600 NF | 3,000 rpm |
|------------|------------------|
| 30F-000 NF | 5.5 hp (3.73 kW) |

This precision semi-automatic programmable sawing system automatically rotates to cut any angle, pushes material into the saw, then automatically rotates to the next desired angle.

STANDARD FEATURES

- · Non-ferrous saw
- Semi automatic operation
- Mitering degree range 22° to 159°
- Feed length available 10' to 30'
- Right-to-Left feed only
- Touch screen controls
- Windows® based software (incudes profile screen)
- Unlimited job storage
- Powered safety hood with safety interlock switch
- Blade door with safety interlock switch Two-year warranty on parts (saw)
- Dual palm buttons
- Adjustable feed rate on saw head

- Two horizontal pneumatic clamps
- Two vertical pneumatic clamps
- Capable of slotting
- One gallon coolant
- Mist coolant lubrication system
- One carbide tipped blade
- Air hose
- Chip collection drawer in base and 4-3/4" chip collection port
- Adjustable leveling pads
- Meets CE standards
- One-year warranty on parts (feed system)
- Saw Made in Spain
- Feed system Made in USA

Straight Cuts – Miter Cuts – and Everything In-Between

OPTIONAL FEATURE

Auto 90° program allows machine to run in full auto mode when cutting at 90°.



Sales partner in México:



ACAT Mexicana

Ave. Regio Parque #200 Regio Parque Industrial Apodaca, Nuevo León, México CP. 66633



acat@acatmexicana.com



(**t**) TEL. 81 8354 8910